

NOTES:

- 1.MATERIAL:
HOUSING: Halogen Free PLASTIC, HIGH TEMP. UL94V-0
TERMINAL: PHOSPER BRONZE(t=0.15)
FITTING NAIL: BRASS(t=0.2)
- 2.PLATING:
CONTACT AND SOLDER: 50u" MIN. NICKEL UNDER RPLATING OVERALL.
1: GOLD FLASH OVER ALL
N: 100~200u" MATTE TIN OVERALL
T: 10U"GOLD ON CONTACT AREA
GOLD FLASH ON SOLDER AREA
C: 15U"GOLD ON CONTACT AREA
GOLD FLASH ON SOLDER AREA
- FITTING NAIL: 50~100 u" NICKEL UNDER PLATING OVERALL.
1: GOLD FLASH
N: 80~100u" MATTE TIN OVERALL
- 3.SPECIFICATION PLS. SEE PS-50208-XXXX
- 4.PACKING REFER TO 88459-XXXX-TRP

P/N LEGEND

50207-XXX X X-XXX


NO OF CKT
PACKING

- 0: TAPE & REEL
- 4: TAPE & REEL (WITH MYLAR)
- 7: TAPE & REEL (WITH COVER)
- 8: TUBE (WITH COVER)

XXX	HOUSING COLOR	LOGO	Halogen free	Packing NO	OTHER
001	BLACK	ACES	HF	88459-XXXX-TRP	WITH MYLARCOVER
				88459-XXXX-06-TRP	WITHOUT MYLARCOVER
002	WHITE	ACES	HF	88459-XXXX-TRP	WITH MYLARCOVER
				88459-XXXX-06-TRP	WITHOUT MYLARCOVER
003	BLACK	ACES	HF	88459-XXXX-U-TRP	WITH MYLARCOVER
004	BLACK	ACES	HF	88459-XXXX-01-TRP	WITH MYLARCOVER

PLATING

- 1: GOLD FLASH OVER ALL(LEAD FREE)
- T: 10U"GOLD ON CONTACT AREA
- N: MATTE TIN
- C: 15u" GOLD ON CONTACT AREA



CKT	Dim A	Dim B	Dim C	Dim D
2	0.80	1.90	3.78	3.04
3	1.60	2.70	4.58	3.84
4	2.40	3.50	5.38	4.64
5	3.20	4.30	6.18	5.44
6	4.00	5.10	6.98	6.24
7	4.80	5.90	7.78	7.04
8	5.60	6.70	8.58	7.84
9	6.40	7.50	9.38	8.64
10	7.20	8.30	10.18	9.44
11	8.00	9.10	10.98	10.24
12	8.80	9.90	11.78	11.04
13	9.60	10.70	12.58	11.84
14	10.40	11.50	13.38	12.64
15	11.20	12.30	14.18	13.44
16	12.00	13.10	14.98	14.24
17	12.80	13.90	15.78	15.04
18	13.60	14.70	16.58	15.84
19	14.40	15.50	17.38	16.64
20	15.20	16.30	18.18	17.44

QUALITY SYMBOLS MAJOR Ⓜ CRITICAL Ⓢ GENERAL TOLERANCES (UNLESS SPECIFIED) X. ±0.5 X ±0.25 .XX ±0.15 .XXX ±0.1 ANGLES ±2°	DRAWN BY GAOLI DATE 22/07/27	
	CHECKED BY XUZHUYONG DATE 22/07/27	
	APPROVED BY XUZHUYONG DATE 22/07/27	UNITS mm SCALE 4:1
		SIZE A4 SHEET NO. 1 OF 1
	DWG NO. N/A REV N SHEET NO. 1 OF 1	PART NO. 50207-XXXXX-XXX