



1. MATERIAL:
 - 1.1 HOUSING: THERMOPLASTIC, HIGH TEMP.UL94V-0; COLOR: WHITE.
 - 1.2 ACTUATOR: THERMOPLASTIC, HIGH TEMP.UL94V-0; COLOR: BLACK.
 - 1.3 CONTACT: COPPER ALLOY
 - 1.4 FITTING NAIL: COPPER ALLOY
2. FINISH:
 - 2.1 CONTACT:
 - 50~100u" NICKEL UNDERPLATING OVERALL.
 - M: 3u" GOLD ON CONTACT AND GOLD FLASH ON SOLDER
 - B: 5u" GOLD ON CONTACT AND GOLD FLASH ON SOLDER
 - T: 10u" GOLD ON CONTACT AND GOLD FLASH ON SOLDER
 - D: 30u" GOLD ON CONTACT AND GOLD FLASH ON SOLDER
 - 2.2 FITTING NAIL:
 - 100~200u" TIN PLATING ON SOLDER TAILS(LEAD FREE).
 - 50~100u" NICKEL UNDERPLATING OVERALL.
3. SPEC. PLS. REFER TO PS-50696-XXXX
4. PACKAGE PLS. REFER TO 50696-XXXX-TRP
5. PART NUMBER

50696-XXX X X-002

NO OF CKT
PACKING
0: TAPE REEL
1: TUBE
A: TAPE & REEL (13" PLASTIC)
D: TAPE & REEL (15" PLASTIC)

CONTACT PLATING

M: 3u" GOLD ON CONTACT AND GOLD FLASH ON SOLDER
B: 5u" GOLD ON CONTACT AND GOLD FLASH ON SOLDER
T: 10u" GOLD ON CONTACT AND GOLD FLASH ON SOLDER
D: 30u" GOLD ON CONTACT AND GOLD FLASH ON SOLDER

CKT	DIM A	DIM B	DIM C	DIM D	DIM E	DIM F	DIM G
4	4.18	1.50	2.57	3.38	3.10	3.90	2.50
5	4.68	2.00	3.07	3.88	3.60	4.40	3.00
6	5.18	2.50	3.57	4.38	4.10	4.90	3.50
7	5.68	3.00	4.07	4.88	4.60	5.40	4.00
8	6.18	3.50	4.57	5.38	5.10	5.90	4.50
9	6.68	4.00	5.07	5.88	5.60	6.40	5.00
10	7.18	4.50	5.57	6.38	6.10	6.90	5.50
11	7.68	5.00	6.07	6.88	6.60	7.40	6.00
12	8.18	5.50	6.57	7.38	7.10	7.90	6.50
13	8.68	6.00	7.07	7.88	7.60	8.40	7.00
14	9.18	6.50	7.57	8.38	8.10	8.90	7.50
15	9.68	7.00	8.07	8.88	8.60	9.40	8.00
16	10.18	7.50	8.57	9.38	9.10	9.90	8.50
17	10.68	8.00	9.07	9.88	9.60	10.40	9.00
18	11.18	8.50	9.57	10.38	10.10	10.90	9.50
19	11.68	9.00	10.07	10.88	10.60	11.40	10.00
20	12.18	9.50	10.57	11.38	11.10	11.90	10.50
21	12.68	10.00	11.07	11.88	11.60	12.40	11.00
22	13.18	10.50	11.57	12.38	12.10	12.90	11.50
23	13.68	11.00	12.07	12.88	12.60	13.40	12.00
24	14.18	11.50	12.57	13.38	13.10	13.90	12.50
25	14.68	12.00	13.07	13.88	13.60	14.40	13.00
26	15.18	12.50	13.57	14.38	14.10	14.90	13.50
27	15.68	13.00	14.07	14.88	14.60	15.40	14.00
28	16.18	13.50	14.57	15.38	15.10	15.90	14.50
29	16.68	14.00	15.07	15.88	15.60	16.40	15.00
30	17.18	14.50	15.57	16.38	16.10	16.90	15.50

QUALITY SYMBOLS MAJOR Ⓢ CRITICAL Ⓢ GENERAL TOLERANCES (UNLESS SPECIFIED) X ±0.50 X ±0.25 .XX ±0.15 .XXX ±0.10 ANGLES ±2°	DRAWN BY Tsal, Wang Kun DATE 23/09/01	
	CHECKED BY Liu, Yuan Huang DATE 23/09/01	
	APPROVED BY Huang, Kuo Hua DATE 23/09/01	UNITS mm SCALE 1:1
	SHEET NO. 1 OF 1	SIZE A4 RFG NO. REV F DWG NO. 50696-XXXX-002