



RECOMMENDED P.C.B. LAYOUT  
TOLERANCE ±0.05 mm

- NOTES:
- MATERIAL:
    - HOUSING: THERMOPLASTIC, HIGH TEMP., UL94V-0; COLOR:BLACK.
    - CONTACT: COPPER ALLOY
  - FINISH:
    - CONTACT: GOLD FLASH OVER ALL.
    - MIN. NICKEL UNDERPLATING OVERALL.
  - SPEC. PLS. REFER TO PS-50972-XXXXX-XXX.
  - PACKING SPEC. PLS. REFER TO 50989-XXXXX-TRP.
  - PART NUMBER

50989-XXX X X-001

NO OF CKT

PACKING

0:TAPE REEL  
1:TUBE PACKAGE  
4:TAPE & REEL With Mylar  
5:TUBE PACKAGE With Mylar

CONTACT PLATING  
1: G/F OVER ALL

一般公差 TOLERANCES X ±0.6 XX ±0.15 X ±0.25 XXX ±0.1 ANGLES 45°		宏致電子股份有限公司 Aces Electronic Co.,Ltd.	
檢驗尺寸標示 SYMBOLS CLASSIFICATION DIMENSION S/R CONN		品名 (TITLE) 2.00MM BATTERY T/H R/A 圖號 (DRAWING NO) 50989-XXXXX-XXX	
MARK IS CRITICAL DIM. MARK IS MAJOR DIM.		製圖 (DRA) 09/10/08 審核 (CHKD) SAM	
表面處理 (FINISH)		核准 (APPD) JASON	
比例 (SCALE) 4:1		張數 (SHEET) 1 OF 1	
單位 (UNITS) mm		尺寸 (SIZE) A4	
		圖號 (REV) 0	