



NOTES:

1. MATERIAL:

1.1 HOUSING: SOMIKASUPER LCP E6808L-BLACK, HIGH TEMP.,UL94V-0

1.2 CONTACT: PHOSPHOR BRONZE

2. FINISH:

CONTACT:

CONTACT:SEE ORDER INFORMATION.

UNDERPLATING: 50~100u" NICKEL OVERALL

3. SPEC. PLS. REFER TO PS-51093-XXXXX-XXX

4. PACKAGE PLS. REFER TO 51087-XXOCR-XX

5. PART NUMBER

51087-XXX X X- XXX

NO OF CKT:

001:NORMAL

DR1:包材使用PLASTIC REEL(膠盤)

PACKING:

0: TAPE & REEL

PLATING:

1:G/F ON CONTACT AND SOLDER

C:15u" GOLD ON CONTACT AND
G/F PLATING ON SOLDER.

RECOMMENDED PCB LAYOUT
GENERAL TOLERANCE ± 0.05

080	19.50	21.80	23.20
070	17.00	19.30	20.70
060	14.50	16.80	18.20
CKT	DIM A	DIM B	DIM C

QUALITY SYMBOLS		DRAWN BY	DATE	ACES ELECTRONICS	
MAJOR	Ⓜ	TSO I CHIAO	21/06/18		
CRITICAL	Ⓢ	CHECKED BY	DATE	TITLE	
GENERAL TOLERANCES (UNLESS SPECIFIED)		Chen, Chun Yuan	21/06/18		
X. ± 0.5		APPROVED BY	DATE	0.50mm PITCH BOARD TO BOARD CONN (PLUG)	
.X ± 0.25		Wang, chun sheng	21/06/18		
.XX ± 0.15		UNITS	mm	SIZE	DWG NO.
.XXX ± 0.1		SCALE	2 : 1	A4	51087-XXXXX-XXX
ANGLES $\pm 2^\circ$		SHEET NO.	1 OF 1	REV	PART NO.
				C	SEE NOTES