

RECOMMENDED PCB LAYOUT
GENERAL TOLERANCE ±0.05

NOTES:

1. MATERIAL:
1.1 HOUSING: SOMIKASUPER LCP E6808L-BLACK, HIGH TEMP.,UL94V-0
1.2 CONTACT: PHOSPHOR BRONZE(C5240-EH)
2. FINISH:
CONTACT:
CONTACT:SEE ORDER INFORMATION.
UNDERPLATING: 50~100μ" NICKEL OVERALL.
3. SPEC. PLS. REFER TO PS-51093-XXXXX-XXX
4. PACKAGE PLS. REFER TO 51090-XXXXR-XX
5. PART NUMBER

51090-XXX X X- XXX

NO OF CKT: [] [] []



001:NORMAL
DR1:包材使用 PLASTIC REEL (膠盤)

PACKING:

- 0: TAPE & REEL
4: T&R WITH MYLAR

PLATING:

- 1:G/F ON CONTACT AND SOLDER
C:15μ" GOLD ON CONTACT AND G/F PLATING ON SOLDER.



80	19.50	21.80	23.20
60	14.50	16.80	18.20
32	7.50	9.80	11.20
CKTS	DIM A	DIM B	DIM C

QUALITY SYMBOLS	DRAWN BY	DATE	
MAJOR	TSO I CHIAO	21/06/18	
CRITICAL	CHECKED BY	DATE	
GENERAL TOLERANCES (UNLESS SPECIFIED)	Chen, Chun Yuan 21/06/18 Wang, chun sheng 21/06/18		TITLE
X. ±0.5 .X ±0.25 .XX ±0.15 .XXX ±0.1 ANGLES ±2'	APPROVED BY	DATE	0.50mm PITCH BOARD TO BOARD CONN (RCPT)
	UNITS	mm	SIZE A4
	SCALE	2:1	DWG NO. 51090-XXXXX-XXX
	SHEET NO.	1 OF 1	REV D
			PART NO. SEE NOTES