





RECOMMENDED PCB LAYOUT
GENERAL TOLERANCE ± 0.05



WITH COVER




NOTES:

1. MATERIAL:
 - 1.1 HOUSING: THERMOPLASTIC, HIGH TEMP., UL94V-0; COLOR:BLACK.
 - 1.2 CONTACT: COPPER ALLOY
 - 1.3 FITTING NAIL : COPPER ALLOY
2. FINISH:
 - 2.1 CONTACT:
 - 1: GOLD PLATED ON CONTACT AND SOLDER AREA
 - 50~100u" MIN NICKEL UNDERPLATING OVERALL
 - 2.2 FITTING NAIL:
 - 80~150u"MIN TIN PLATING OVERALL,
 - 50~100u" MIN NICKEL UNDERPLATING OVERALL
3. REFLOW SOLDER CAPABLE TO 260°C PER ACES SPEC.
4. WAVE SOLDER CAPABLE TO 260°C PER ACES SPEC.
5. SPEC. PLS. REFER TO PS-50975-xxxxx-xxx
6. PACKAGE PLS. REFER TO 51983-xxxxx-TRP


7. PART NUMBER

P/N LEGEND



PACKING 0:TAPE & REEL
7:TAPE & REEL WITH COVER

PLATING 1:GOLD PLATED ON CONTACT AND SOLDER AREA



一般公差 TOLERANCES X ± 0.50 .XX ± 0.15 X ± 0.25 .XXX ± 0.10 ANGLES $\pm 2^\circ$		宏致電子股份有限公司 Aces Electronic Co.,Ltd.	
檢驗尺寸標示 SYMBOLS Ⓢ Ⓜ INDICATE CLASSIFICATION DIMENSION Ⓢ MARK IS CRITICAL DIM. Ⓜ MARK IS MAJOR DIM.	品名 (TITLE) 2.00mm Battery Conn. Male DIP R/A Type H=3.3 圖號 (DWG.NO) 51983-XXXXX-XXX	製圖 (DR) 02/28/11' Brave	審核 (CHKD) Sam
表面處理 (FINISH)	比例 (SCALE) 2:1	單位 (UNITS) mm	核准 (APPD) Jason
			張數 (SHEET) 1 OF 1
			尺寸 (SIZE) A4
			版數 (REV) 1