



RECOMMENDED PCB LAYOUT
GENERAL TOLERANCE ± 0.05



WITH COVER



NOTES:

1. MATERIAL:

- 1.1 HOUSING: THERMOPLASTIC, HIGH TEMP., UL94V-0; COLOR:BLACK.
- 1.2 CONTACT: COPPER ALLOY
- 1.3 FITTING NAIL : COPPER ALLOY

2. FINISH:

2.1 CONTACT:

1: GOLD PLATED ON CONTACT AND SOLDER AREA
50~100u" MIN NICKEL UNDERPLATING OVERALL

2.2 FITTING NAIL:

80~150u" MIN TIN PLATING OVERALL,
50~100u" MIN NICKEL UNDERPLATING OVERALL

3. REFLOW SOLDER CAPABLE TO 260°C

PER ACES SPEC.

4. WAVE SOLDER CAPABLE TO 260°C

PER ACES SPEC.

5. SPEC. PLS. REFER TO PS-50975-xxxxx-xxx

6. PACKAGE PLS. REFER TO 51984-xxxxx-xx-TRP

7. PART NUMBER

P/N LEGEND

51984-XXX	X	X	-XXX	XXX Housing Color
007: 7PIN				001 Black


PACKING

0:TAPE & REEL

7:TAPE & REEL WITH COVER

PLATING

1:GOLD PLATED ON CONTACT
AND SOLDER AREA



TOLERANCES X ± 0.50 .XX ± 0.15 X ± 0.25 .XXX ± 0.10 ANGLES $\pm 2^\circ$		宏致電子股份有限公司 Aces Electronic Co.,Ltd.	
檢驗尺寸標示	品名 (TITLE) 2.00mm Battery Conn. Male DIP R/A Type H=4.8	製圖 (DR) 07/22/11'	Brave
SYMBOLS \oplus \ominus INDICATE CLASSIFICATION DIMENSION	圖號 (DWG.NO) 51984-XXXXX-XXX	審核 (CHKD)	Sam
\oplus MARK IS CRITICAL DIM. \ominus MARK IS MAJOR DIM.	核准 (APPD)	Jason	
表面處理 (FINISH)	比例 (SCALE) 2:1	單位 (UNITS) mm	張數 (SHEET) 1 OF 1
			SIZE A4
			REV 0