


RECOMMEND PCB LAYOUT
TOLERANCE ±0.05mm



NOTES:

- MATERIAL:
 - HOUSING: THERMOPLASTIC, HIGH TEMP., UL94V-0.
 - CONTACT: COPPER ALLOY.
 - HOOK: COPPER ALLOY.
- FINISH:
 - CONTACT:
 - 50u" MIN. NICKEL UNDERPLATING OVERALL.
 - P:GOLD PLATED ON CONTACT AND SOLDER TAIL AREA
 - GOLD PLATED ON CONTACT FOR
 - 120u" MIN MATT TIN ON SOLDER
 - HOOK:
 - 50u" MIN. NICKEL UNDER PLATING OVER ALL
 - 100u" MIN MATT TIN PLATING OVER ALL
- REFLOW SOLDER CAPABLE TO 260°C PER ACES SPEC.
- SPEC. PLS REFER TO PS-53006-XXXXX-XXX
- PACKAGE PLS REFER TO 53005-XXXXX-XX-TRP
- PART NUMBER

53005-XXX X X-XXX

CKTS
008: 8PIN

PACKING
0:TAPE REEL
1:TUBE

XXX	Material&Color
001	LCP&Black

PLATING
P:GOLD FLASH
2:GOLD FLASH ON CONTACT(LEAD FREE)

CKTS	DIM A	DIM B	DIM C	DIM D
8	14.00	25.10	20.60	18.10

一般公差 TOLERANCES X ±0.5 XX ±0.15 X ±0.25 XXX ±0.1 ANGLES ±2°		宏致電子股份有限公司 Aces Electronics Co.,Ltd.	
檢驗尺寸標示 SYMBOLS INDICATE CLASSIFICATION DIMENSION MARK IS CRITICAL DIM. MARK IS MAJOR DIM.	品名 (TITLE) 2.00mm Battery Conn. Female SMT R/A Type	製圖 (DR) 許紅璽 '12/12/17 審核 (CHKD) CARL 核准 (APPD) Jason	圖號 (DWG NO.) 53005-XXXXX-XXX
表面處理 (FINISH)	比例 (SCALE) 1:1	單位 (UNITS) mm	張數 (SHEET) 1 OF 1 SIZE A4 REV 0