

RECOMMENDED P.C.B. LAYOUT T=1.2mm
TOLERANCE ±0.05 mm

NOTES:

1. MATERIAL:

- 1.1 HOUSING: THERMOPLASTIC, HIGH TEMP.,UL94V-0.
- 1.2 CONTACT: COPPER ALLOY.
- 1.3 HOOK: COPPER ALLOY.

2. FINISH:

- 2.1 CONTACT & SOLDER:
50~100u" NICKEL UNDERPLATING OVERALL.
1:GOLD FLASH ON CONTACT AND SOLDER TAIL AREA.
- 2.2 HOOK:
50~100u" NICKEL UNDER PLATING OVER ALL
100~200u" MATTE TIN PLATING

- 3. REFLOW SOLDER CAPABLE TO 260°C
PER ACES SPEC.

- 4. SPEC.PLS REFER TO PS-54955-XXXX-XXX


- 5. PACKAGE PLS REFER TO 54955-XXXX-XX-TRP

- 6. PART NUMBER



54955-XXX X X-XXX

NO. OF CKTS 006:6PIN	XXX	Housing Color	Cover Color
	001	Black	White

- PACKING
- 7:TAPE & REEL WITH COVER
 - 8:TUBE & REEL WITH COVER
- PLATING
1: GOLD FLASH ON CONTACT AND SOLDER TAIL AREA



WITH COVER



一般公差 TOLERANCES X ±0.5 XX ±0.15 X ±0.25 XXX ±0.1 ANGLES ±2°		宏致電子股份有限公司 Aces Electronics Co.,Ltd.	
檢驗尺寸標示 SYMBOLS INDICATE CLASSIFICATION DIMENSION	品名 (TITLE) 2.00mm Battery Conn. Male DIP S/T Type H=4.85	製圖 (DR) 13/5/30 CHENBO	核准 (CHKD) CARL
MARK IS CRITICAL DIM. MARK IS MAJOR DIM.	圖號 (DWG NO.) 54955-xxxxx-xxx-TRP-aces	核准 (APPD) Jason	張數 (SHEET) 1 OF 1
表面處理 (FINISH)	比例 (SCALE) 1:1	單位 (UNITS) mm	圖號 (DWG NO.)
			SIZE A4
			REV 0