



RECOMMENDED PCB LAYOUT
GENERAL TOLERANCE ±0.05

NOTES:

1. MATERIAL:
 - 1.1 HOUSING: THERMOPLASTIC, HIGH TEMP(LCP),, UL94V-0; COLOR:BLACK.
 - 1.2 CONTACT: COPPER ALLOY (C2680)
 - 1.3 FITTING NAIL:COPPER ALLOY
2. FINISH:
 - 2.1 CONTACT:
 - 50u" MIN. NICKEL UNDERPLATING OVERALL
 - N:60u" MIN MATTE TIN OVERALL
3. REFER TO PS-57957-XXXX-XXX
4. PACKAGE PLS. REFER TO 56968-XXXX-XX-TRP
5. PART NUMBER

56968-XXX X X-XXX

NO OF CKT X X-XXX 001:NORMAL
 PACKING X PLATING
 0:TAPE&REEL N:MATTE TIN

CKT	DIM A	DIM B	DIM C
6	21.65	15.00	26.20

QUALITY SYMBOLS MAJOR CRITICAL GENERAL TOLERANCES (UNLESS SPECIFIED) X. ±0.5 .X ±0.36 .XX ±0.25 .XXX ±0.15 ANGLES ±2°	DRAWN BY Tang,En Hui DATE 18/09/12			
	CHECKED BY Lu,Jing Quan DATE 18/09/12		TITLE 3.0mm PITCH WTB HEADER CONN. SMT S/R R/A TYPE	
	APPROVED BY hsieh,fu yu DATE 18/09/12	UNITS mm	SIZE A4	RFC NO. N/A
	SCALE 3:1	SHEET NO. 1 OF 1	REV A	DWG NO. 56968-XXXX-XXX