



RECOMMENDED PCB LAYOUT (COMPONENT SIDE)  
(TOLERANCE: ±0.05)

- NOTES:  
 1.MATERIAL:  
 1.1 HOUSING: SEE TABLE  
 1.2 CONTACTS: SEE TABLE  
 2.FINISH:  
 2.1 CONTACT: SEE P/N  
 3.THE CONNECTOR IS RoHS COMPLIANT.  
 4.BURR IS 0.5mm MAX.  
 5.SPEC. PLS. REFER TO PS-60006-XXXXX-XXX  
 6.PACKAGE: BAG  
 7.P/N: 60006-XXX X X-001

CKTS ————  
 004~050 PINS  
 PACKING ————  
 3: BAG  
 PLATING:  
 1:GOLD FLASH OVER ALL

B	TERMINAL		COPPER ALLOY	SEE P/N
A	HOUSING	1	NY6T	UL 94V-0, BLACK
NO	DESCRIPTION	Q'TY	MATERIAL	PLATING & COLOR
QUALITY SYMBOLS		DRAWN BY	DATE	
MAJOR Ⓢ		LYU JIA YING	'20/10/21	
CRITICAL Ⓢ		CHECKED BY	DATE	
GENERAL TOLERANCES (UNLESS SPECIFIED)		TENG CHANG HO	'20/10/21	
		APPROVED BY	DATE	TITLE
		KUO JUNG HSUN	'20/10/21	1.27mm PIN HEADER CONN. T/H S/R S/T TYPE
		UNITS	SIZE	RFQ NO.
		mm	A4	N/A
		SCALE	SHEET NO.	DWG NO.
		X: X	1 OF 1	60006-XXXXX-XXX

TOLERANCES:  
±0.30