



RECOMMENDED PCB LAYOUT (COMPONENT SIDE)
(TOLERANCE: ±0.05)

DIM. D	DIM. C	CKTS
3.00mm	3.85mm	006
4.20mm	3.40mm	008~080

- NOTES:
- MATERIAL:
 - HOUSING: SEE TABLE
 - CONTACTS: SEE TABLE
 - COVER: SEE TABLE
 - FINISH:
 - CONTACT: SEE P/N
 - THE CONNECTOR IS RoHS COMPLIANT.
 - BURR IS 0.5mm MAX.
 - SPEC. PLS. REFER TO PS-60192-XXXXX-XXX
 - PACKAGE PLS. REFER TO 60235-XXXXX-XXX-PCK
 - P/N: 60235-XXX X X-001

CKTS ————
006~026 PINS

PACKING ————
7: TAPE & REEL WITH COVER

PLATING:
1:GOLD FLASH OVER ALL

CKTS	A	B
004	1.00	2.50
006	2.00	3.50
008	3.00	4.50
010	4.00	5.50
012	5.00	6.50
014	6.00	7.50
016	7.00	8.50
018	8.00	9.50
020	9.00	10.50
022	10.00	11.50
024	11.00	12.50
026	12.00	13.50
028	13.00	14.50
030	14.00	15.50
032	15.00	16.50

NO	DESCRIPTION	Q'TY	MATERIAL	PLATING & COLOR
C	COVER	1	STAINLESS STELL	N/A
B	TERMINAL		COPPER ALLOY	SEE P/N
A	HOUSING	1	LCP	UL 94V-0, BLACK

QUALITY SYMBOLS MAJOR Ⓜ CRITICAL Ⓢ GENERAL TOLERANCES (UNLESS SPECIFIED) X. ±0.5 .XX ±0.25 .XX ±0.15 .XXX ±0.1 ANGLES ±2°	DRAWN BY LIAO WAN TING CHECKED BY TENG CHANG HO APPROVED BY KUO JUNG HSUN	DATE '20/11/27 DATE '20/11/27 DATE '20/11/27	
	UNITS mm SCALE X: X	SHEET NO. 1 OF 1	