



SECTION A-A


- NOTES:
1. MATERIAL: C5210-1/2H, THICKNESS 0.25±0.01 .
 2. PLATING:
 - L: 10~30u" NICKEL UNDERPLATING
 - 50~100u" TIN PLATING(PURE TIN)
 3. APPLICABLE WIRE RANGE: 0.5mm² AVSS;
 4. ALL UNSPECIFIED CORNERS AND RADIUS NOT TO EXCEED R0.1mm;
 5. SPEC. PLUS REFER TO SPEC-92415-XXXXX-XXX;
 6. TOLERANCES:
7. PART NUMBER
92527-T 0 X X-CA1
- | | | |
|------|-------|-------|
| 0~10 | 10~30 | ANGLE |
| 0.20 | 0.25 | ±3° |
- 2: C5210 1/2H PLATING
L: PURE TIN



SECTION B-B



SECTION C-C



QUALITY SYMBOLS		DRAWN BY		DATE	
MAJOR	MINOR	Xuyangyong	20/01/06		
CRITICAL		CHECKED BY	DATE		
		Liuwei	20/01/06		
GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVED BY		TITLE	
X	±0.50	Liuwei	20/01/06	040 Auto Female Terminal/Receptacle Ty	
XX	±0.25			SIZE	REQ. NO.
XXX	±0.10			A4	SEE NOTES
ANGLES	±2°			SCALE	DWG. NO.
				1:1	92527-TOXX-CA1
				1 OF 1	

