



## SPECIFICATION

宏致電子股份有限公司

桃園縣中壢市東園路 13 號

No.13, Dongyuan Rd., Jhongli City,

Taoyuan County 320, Taiwan (R.O.C.)

TEL: +886-3-463-2808

FAX: +886-3-463-1800

**SPEC. NO.:** PS-31863-XXXXX-001

**REVISION:** C

**PRODUCT NAME:** 0.5 mm PITCH USB TYPE C CONN.

**PRODUCT NO:** 318XX SERIES

|   |   |  |
|---|---|--|
| PREPARED:<br><br>Hsu, Wei Chun<br><br>DATE:<br>2023.05.03 | CHECKED:<br><br>Chang, Chun Te<br><br>DATE:<br>2023.05.03 | APPROVED:<br><br>Kuo, Rong Hsun<br><br>DATE:<br>2023.05.03 |
|---|---|--|



**TITLE: 0.5 MM PITCH USB TYPE C CONN.**

**1. REVISION HISTORY .....3**

**2. SCOPE .....4**

**3. APPLICABLE DOCUMENTS .....4**

**4. REQUIREMENT .....4**

**5. PERFORMANCE .....5**

**6. PRIMARY QUALIFICATION APPROVAL TESTING .....10**

**7. GROUP TEST METHOD .....13**

**8. HOT AIR REFLOW CONDITION .....25**

Aces P/N: **318XX SERIES**TITLE: **0.5 MM PITCH USB TYPE C CONN.**

RELEASE DATE: 2023.05.03

8REVISION: C

ECN No: ECN-012221

PAGE: **3** OF **25****1 Revision History**

| Rev. | ECN #      | Revision Description   | Prepared      | Date       |
|------|------------|--|---------------|------------|
| A    | ECN-000948 | New product specification  | Hsu, Wei Chun | 2020.10.28 |
| B    | ECN-004870 | 1. Modify Rated Voltage: DC 48V.<br>2. The mixed flowing gas is increased (Only for 30u" Au and 2u" Au + 30u" NiPd plating) Description.   | Hsu, Wei Chun | 2021.11.03 |
| C    | ECN-012221 | Modify :<br>(A) Insulation Resistance (P5/P20).<br>(B) Extraction force (P19).<br>(C) Hot air reflow condition (P25).<br>Add :<br>(A) Resistance to Reflow Soldering Heat (P9).<br>(B) Salt Spray (Only For Gold Plating) (P9)<br>(C) Group 8 (P11). | Hsu, Wei Chun | 2023.05.03 |

## 2 SCOPE

This specification covers performance, tests and quality requirements for 0.5mm pitch USB Type C connector.

Aces' P/N: Receptacle : 318XX  
Plug : 318XX

## 3 APPLICABLE DOCUMENTS

Universal Serial Bus Type-C Cable and Connector Specification  
EIA-364 : ELECTRONICS INDUSTRIES ASSOCIATION

## 4 REQUIREMENTS

### 4.1 Design and Construction

Product shall be of design, construction and physical dimensions specified on applicable product drawing.

### 4.2 Materials and Finish

- 4.2.1 Contact: High performance Copper alloy  
Finish: Refer to the drawing.
- 4.2.2 Housing: Thermoplastic, High temp. UL94 V-0
- 4.2.3 Shell: Stainless steel  
Finish: Refer to the drawing.
- 4.2.4 Receptacle Mid-Plate: Stainless steel  
Finish: Refer to the drawing.
- 4.2.5 Plug Side Latch: Stainless steel  
Finish: Refer to the drawing.
- 4.2.6 Plug EMC Spring: Stainless steel  
Finish: Refer to the drawing.

### 4.3 Ratings

- 4.3.1 Rated voltage: DC 48 V
- 4.3.2 Current:  
A current of 9 A shall be applied collectively to  $V_{BUS}$  pins (i.e., pins A4, A9, B4, and B9) and 1.25 A shall be applied to the  $V_{CONN}$  pin (i.e., B5) as applicable, terminated through the corresponding GND pins (i.e., pins A1, A12, B1, and B12). A minimum current of 0.25 A shall also be applied individually to all the other contacts, as applicable.
- 4.3.3 Operating Temperature : -40°C to +85°C

## 5 Performance

### 5.1. ELECTRICAL REQUIREMENTS

| <b>ELECTRICAL</b>                         |   |  |
|---|---|--|
| <b>Item</b>                               | <b>Test Condition</b>   | <b>Requirement</b>   |
| <b>Low Level Contact Resistance(LLCR)</b> | EIA-364-23<br>The measurement is made across the plug and receptacle mated contacts and does not include any internal paddle cards or substrates of the plug or receptacle.<br>Measure at 20 mV (Max) open circuit at 100 mA.   | 40 mΩ (max) initial for all pin<br><br>50 mΩ (max) after initial measurement.  |
| <b>Insulation Resistance</b>              | EIA 364-21.<br>Mated and unmated connectors, apply 500 V DC between adjacent terminals.<br>Applicable to both receptacle and plug.  | A minimum of 100 MΩ insulation resistance  |
| <b>Dielectric Withstanding Voltage</b>    | EIA-364-20<br>The dielectric shall withstand 100 VAC (RMS) for one minute at sea level after the environmental stress   | No disruptive discharge<br>Current leakage: 1 mA max.  |
| <b>Contact Current Rating</b>             | Mate connector: measure the temperature rise at rated current after:<br>A current of 9 A shall be applied collectively to V <sub>BUS</sub> pins (i.e., pins A4, A9, B4, and B9) and 1.25 A shall be applied to the V <sub>CONN</sub> pin (i.e., B5) as applicable, terminated through the corresponding GND pins (i.e., pins A1, A12, B1, and B12). A minimum current of 0.25 A shall also be applied individually to all the other contacts<br>The ambient condition is still air at 25° C (EIA-364-70 METHOD 2) | When current is applied to the contacts, the temperature rise shall not exceed 30°C at the outside surface of the shell. |

## 5.2 MECHANICAL REQUIREMENTS

| <b>MECHANICAL</b>                   |   |  |
|-------------------------------------|---|--|
| <b>Item</b>                         | <b>Test Condition</b>   | <b>Requirement</b>   |
| <b>Insertion Force</b>              | EIA 364-13<br>Mate connector, At a maximum rate of 12.5 mm (0.492") per minute.   | Within the range of 5 N to 20 N..  |
| <b>Extraction Force</b>             | EIA 364-13<br>Un-mate connector, At a maximum rate of 12.5mm (0.492") per minute.   | Initial:<br>Within the range of 8 N to 20 N.<br><br>After Test:<br>Within the range of 6 N to 20 N   |
| <b>Durability</b>                   | The durability rating shall be 10,000 cycles minimum for the USB Type-C connector family. The durability test shall be done at a rate of 500+/-50 cycles per hour and no physical damage to any part of the connector and cable assembly shall occur.<br>(EIA-364-09) | No physical damage<br><br>Contact resistance:<br>50 mΩ Max. After initial measurement<br><br>Dielectric withstanding voltage:<br>No disruptive discharge.<br>Current leakage: 1 mA max.<br><br>Insulation Resistance:<br>100 MΩ min.<br><br>Extraction Force:<br>Within the range of 6 N to 20 N |
| <b>Durability (preconditioning)</b> | Perform 50 unplug/plugin cycles<br>(EIA-364-09)   | No physical damage   |
| <b>Vibration</b>                    | EIA-364-28, test condition VII, test condition letter D, 15 minutes in each of 3 mutually perpendicular directions. Both mating halves should be rigidly fixed so as not to contribute to the relative motion of one contact against another.                         | No evidence of physical damage.<br>No discontinuities of 1 μs or longer duration when mated connector during test.<br><br>Contact resistance : 50 mΩ Max   |
| <b>4-Axis Continuity Test</b>       | -The PCB shall be clamped on three sides of the receptacle no further than 5 mm away from the receptacle outline.<br>- 5 mm ball tipped probe applied the force<br>- Duration : 10 seconds<br>- Direction: four directions (i.e., left, right, up, and down).         | No discontinuities greater than 1 microsecond duration in any of the four orientations tested.   |



Aces P/N: **318XX SERIES**

**TITLE: 0.5 MM PITCH USB TYPE C CONN.**

RELEASE DATE: 2023.05.03

8REVISION: C

ECN No: ECN-012221

PAGE: **7** OF **25**

|                       |  |  |
|-----------------------|--|--|
| <b>Wrenching Test</b> | <ul style="list-style-type: none"><li>- Plug only</li><li>- Direction: four directions (i.e., left, right, up, and down).</li><li>- Duration: 10 seconds</li></ul> | <p>The plug shall be mated with the continuity test fixture after the test forces have been applied to verify no damage has occurred that causes discontinuity or shorting.</p> <p>No plug damage: 0.75 Nm.<br/>No discontinuity or short after the test force applied.</p> <p>Dielectric withstanding voltage:<br/>No disruptive discharge for 100VAC(rms)</p> <p>The plug shall disengage from the test fixture or mechanically fail when a moment of 2.0 Nm is applied in the up and down directions and a moment 3.5 Nm is applied in the left and right directions.</p> |
|-----------------------|--|--|

### 5.3 ENVIRONMENTAL REQUIREMENTS

| ENVIRONMENTAL  |   |   |
|--|---|---|
| Item   | Test Condition  | Requirement   |
| <b>Temperature life</b>  | EIA-364-17, method A<br>105° C without applied voltage for 120 hours.   | No evidence of physical damage.<br>Contact resistance: 50 mΩ Max. |
| <b>Temperature life (preconditioning)</b>                                    | EIA-364-17, method A<br>105° C without applied voltage for 72 hours.  | No evidence of physical damage.<br>Contact resistance: 50 mΩ Max. |
| <b>Thermal shock</b>   | EIA-364-32, test condition I<br>10 cycles with the exception of exposure times. Place a thermocouple in the center of the largest mass component of the connector that is in the center of the test chamber to insure that the contacts reach the temperature extremes before ramping to the other temperature.   | No evidence of physical damage.<br>Contact resistance: 50 mΩ Max. |
| <b>Mixed flowing gas ( Only for 30u" Au and 2u" Au + 30u" NiPd plating )</b> | EIA-364-65, class II Condition A<br><br>Mate connectors, and subject to the mixed flowing gas conditions.<br>1)expose 1/2 of the specimens unmated for 2/3 of the test duration<br>2)mate each specimen to the same plug that it was mated to during temperature life (preconditioning); and,<br>3) expose for the remainder of the test duration.<br>Duration: 7 day | No evidence of physical damage.<br>Contact resistance: 50 mΩ Max. |
| <b>Thermal disturbance</b>   | Cycle the connector or socket between 15 °C ±3 °C and 85 °C ± 3 °C, as measured on the part. Ramps should be a minimum of 2 °C per minute, and dwell times should insure that the contacts reach the temperature extremes (a minimum of 5 minutes). Humidity is not controlled. Perform 10 such cycles.   | Contact resistance: 50 mΩ Max.                                    |



**TITLE: 0.5 MM PITCH USB TYPE C CONN.**

RELEASE DATE: 2023.05.03

8REVISION: C

ECN No: ECN-012221

PAGE: **9** OF **25**

|  |   |  |
|--|---|--|
| <b>Cyclic temperature and humidity</b>     | EIA-364-31<br>Cycle the connector between 25 °C ±3 °C at 80 % ±3% RH and 65 °C ±3 °C at 50 % ±3% RH. Ramp times should be 0.5 hour and dwell times should be 1.0 hour. Dwell times start when the temperature and humidity have stabilized within the specified levels. Perform 24 such cycles. | No mechanical damage.<br>Contact resistance: 50 mΩ Max.<br><br>Insulation resistance:<br>100 MΩ min.<br><br>Dielectric withstanding voltage:<br>No disruptive discharge.<br>Current leakage: 1 mA max. |
| <b>Reseating</b>                           | Manually unplug/plug the connector. Perform 3 such cycles.  | No physical damage   |
| <b>Salt Spray (Only For Gold Plating)</b>  | See Test Group A_EIA 364-1000.1 and Group A-8   | Subject mated/unmated connectors to 5% salt-solution concentration, 35°C.<br>(I) Gold flash for 8 hours.<br>(II) Gold plating over 5 u" for 48 Hours.<br>(EIA-364-26)                                  |
| <b>Resistance to Reflow Soldering Heat</b> | Resistance to Reflow Soldering Heat   | Pre Heat: 150°C~200°C ,<br>60 ~120 sec.<br>Heat: 217°C Min. , 100 sec. Min.<br>255°C Min. , 30 sec. Min.<br>Peak Temp.: 260°C Max.<br><br>Reflow number cycle: 2 time                                  |



Aces P/N: **318XX SERIES**

**TITLE: 0.5 MM PITCH USB TYPE C CONN.**

RELEASE DATE: 2023.05.03

8REVISION: C

ECN No: ECN-012221

PAGE: **10** OF **25**

## 6 PRIMARY QUALIFICATION APPROVAL TESTING

| Test Group            | Title   | Number of Specimens |                               |
|-----------------------|---|---------------------|-------------------------------|
|                       |   | Receptacle          | Plug                          |
| <b>Test Group A</b>   | Reliability test EIA 364-1000.01<br>(A-1/A-2 / A-3 / A-4 / A-7)           | 30pcs               | 30pcs                         |
| <b>Test Group B-1</b> | Mechanical test<br>(B-1-4 : 4-Axis Continuity)                            | B-1-4 only ,8 pcs   | B-1-4 only ,8 pcs             |
| <b>Test Group B-5</b> | B-5-1 : Critical Dimensions<br>B-5-2 : EMC Shielding Spring<br>Inspection | 3                   | 3                             |
| <b>Test Group B-6</b> | Connector Pair Current Rating   | 3                   | 3                             |
| <b>Test Group B-7</b> | Plug connector Wrenching test   | N/A                 | B-7-1 ,3 pcs<br>B-7-4 ,12 pcs |

**TITLE: 0.5 MM PITCH USB TYPE C CONN.**

RELEASE DATE: 2023.05.03

8REVISION: C

ECN No: ECN-012221

PAGE: **11** OF **25**

## 6.1 Test Group A\_EIA 364-1000.1

| Group 1<br>5 sample         | Group 2<br>5 sample                      | Group 3<br>5 sample   | Group 4<br>5 sample    | Group 7<br>5 sample                   | Group 8<br>5 sample |
|-----------------------------|--|-----------------------|------------------------|---------------------------------------|---------------------|
| Examination                 | Examination                              | Examination           | Examination            | Dielectric<br>withstanding<br>voltage | Examination         |
| LLCR                        | LLCR                                     | LLCR                  | LLCR                   | LLCR                                  | Salt spray          |
| Durability<br>(50cyc)       | Durability<br>(50cyc)                    | Durability<br>(50cyc) | Durability<br>(50cyc)  | Insertion<br>Force                    | Examination         |
| Temperature<br>life (120hr) | Thermal Shock                            | Temp Life<br>(72hr)   | Temp Life<br>(72hr)    | Extraction<br>Force                   |                     |
| LLCR                        | LLCR                                     | LLCR                  | LLCR                   | Durability                            |                     |
| Reseating(3cyc)             | Cyclic<br>temperature<br>and<br>Humidity | Vibration             | Mixed flowing<br>gas   | Extraction<br>Force                   |                     |
| LLCR                        | LLCR                                     | LLCR                  | LLCR                   | Durability<br>(10k)                   |                     |
|                             | Reseating(3cyc)                          |                       | Thermal<br>Disturbance | Extraction<br>Force                   |                     |
|                             | LLCR                                     |                       | LLCR                   | LLCR                                  |                     |
|                             |  |                       | Reseating(3cyc)        | Dielectric<br>withstanding<br>voltage |                     |
|                             |  |                       | LLCR                   | Insulation<br>Resistance              |                     |


**EIA test groups A-5 and A-6 do not apply to this connector**

## 6.2 Test Group B

| Group B-1<br>Mechanical                               | Group B-2<br>USB 2.0 and Low<br>speed Mechanical     | Group B-3<br>SS signal<br>Testing | Group B-4<br>Cable<br>Shielding | Group B-5<br>Critical<br>Dimensions      | Group B-6                    | Group B-7<br>Wrenching<br>Test                                   |
|---|--|-----------------------------------|---------------------------------|--|------------------------------|--|
| Cable Pull<br>out<br>(For cable<br>assembly<br>only.) | Applicable to Type-C Cable and Adaptor<br>Assemblies |                                   |                                 | Critical<br>Dimensions                   | Contact<br>Current<br>Rating | Wrenching<br>Strength<br>(For Plug<br>Connector)                 |
| Cable Flex<br>(For cable<br>assembly<br>only.)        |  |                                   |                                 | EMC<br>Shielding<br>Spring<br>Inspection |                              | Continuity<br>(For Plug<br>Connector)                            |
| 4-Axis<br>Continuity                                  |  |                                   |                                 |  |                              | Dielectric<br>withstanding<br>voltage<br>(For Plug<br>Connector) |
| Voltage<br>drop<br>(For cable<br>assembly<br>only.)   |  |                                   |                                 |  |                              | Wrenching<br>Strength<br>(For Plug<br>Connector)                 |
| Visual<br>inspection<br>(cable/wire)                  |  |                                   |                                 |  |                              |  |

## 7 GROUP TEST METHOD

### Test Group A-1 (required for all connectors)

| Item | Test                         | Test procedure   | Test criteria   |
|------|------------------------------|--|---|
| 1    | Low level contact resistance | <p>EIA-364-23<br/>The measurement is made across the plug and receptacle mated contacts and does not include any internal paddle cards or substrates of the plug or receptacle.<br/>Measure at 20 mV (Max) open circuit at 100 mA.</p> <p>LLCR measurement of pin "A1"</p>  | 40 milliohms max for all contacts.<br>Baseline measurement. |
| 2    | Durability (preconditioning) | EIA-364-09<br>Perform 50 unplug/plug cycles.   | No evidence of physical damage                              |
| 3    | Temperature life             | EIA-364-17, method A<br>105° C without applied voltage for 120 hours.  | None  |
| 4    | Low level contact resistance | EIA-364-23<br>The measurement is made across the plug and receptacle mated contacts and does not include any internal paddle cards or substrates of the plug or receptacle.  | 50 milliohms max.   |
| 5    | Reseating                    | Manually unplug/plug the connector or socket.<br>Perform 3 such cycles.  | No evidence of physical damage                              |
| 6    | Low level contact resistance | EIA-364-23<br>The measurement is made across the plug and receptacle mated contacts and does not include any internal paddle cards or substrates of the plug or receptacle.  | 50 milliohms max.   |

Aces P/N: **318XX SERIES**TITLE: **0.5 MM PITCH USB TYPE C CONN.**

RELEASE DATE: 2023.05.03

8REVISION: C

ECN No: ECN-012221

PAGE: **14** OF **25****Test Group A-2 (required for all connectors)**

| Item | Test                         | Test procedure   | Test criteria   |                  |  |                 |                |   |                 |        |   |                 |       |   |               |        |   |                 |       |      |
|------|------------------------------|--|---|------------------|--|-----------------|----------------|---|-----------------|--------|---|-----------------|-------|---|---------------|--------|---|-----------------|-------|------|
| 1    | Low level contact resistance | EIA-364-23<br>The measurement is made across the plug and receptacle mated contacts and does not include any internal paddle cards or substrates of the plug or receptacle.  | 40 milliohms max for all contacts.<br>Baseline measurement. |                  |  |                 |                |   |                 |        |   |                 |       |   |               |        |   |                 |       |      |
| 2    | Durability (preconditioning) | EIA-364-09<br>Perform 50 unplug/plug cycles.   | No evidence of physical damage                              |                  |  |                 |                |   |                 |        |   |                 |       |   |               |        |   |                 |       |      |
| 3    | Thermal shock                | EIA-364-32, test condition I<br>10 cycles with the exception of exposure times.<br>Place a thermocouple in the center of the largest mass component of the connector that is in the center of the test chamber to insure that the contacts reach the temperature extremes before ramping to the other temperature.<br><table><tr><th rowspan="2">Step</th><th colspan="2">Test condition I</th></tr><tr><th>Temperature, °C</th><th>Time , minutes</th></tr><tr><td>1</td><td>+0<br/>-55<br/>-3</td><td>30 min</td></tr><tr><td>2</td><td>+10<br/>25<br/>-5</td><td>5 max</td></tr><tr><td>3</td><td>+3<br/>85<br/>0</td><td>30 min</td></tr><tr><td>4</td><td>+10<br/>25<br/>-5</td><td>5 max</td></tr></table> | Step  | Test condition I |  | Temperature, °C | Time , minutes | 1 | +0<br>-55<br>-3 | 30 min | 2 | +10<br>25<br>-5 | 5 max | 3 | +3<br>85<br>0 | 30 min | 4 | +10<br>25<br>-5 | 5 max | None |
| Step | Test condition I             |  |   |                  |  |                 |                |   |                 |        |   |                 |       |   |               |        |   |                 |       |      |
|      | Temperature, °C              | Time , minutes   |   |                  |  |                 |                |   |                 |        |   |                 |       |   |               |        |   |                 |       |      |
| 1    | +0<br>-55<br>-3              | 30 min   |   |                  |  |                 |                |   |                 |        |   |                 |       |   |               |        |   |                 |       |      |
| 2    | +10<br>25<br>-5              | 5 max  |   |                  |  |                 |                |   |                 |        |   |                 |       |   |               |        |   |                 |       |      |
| 3    | +3<br>85<br>0                | 30 min   |   |                  |  |                 |                |   |                 |        |   |                 |       |   |               |        |   |                 |       |      |
| 4    | +10<br>25<br>-5              | 5 max  |   |                  |  |                 |                |   |                 |        |   |                 |       |   |               |        |   |                 |       |      |
| 4    | Low level contact resistance | EIA-364-23<br>The measurement is made across the plug and receptacle mated contacts and does not include any internal paddle cards or substrates of the plug or receptacle.  | 50 milliohms max.   |                  |  |                 |                |   |                 |        |   |                 |       |   |               |        |   |                 |       |      |

**TITLE: 0.5 MM PITCH USB TYPE C CONN.**

RELEASE DATE: 2023.05.03


8REVISION: C

ECN No: ECN-012221

PAGE: **15** OF **25**
**5**
**Cyclic  
temperature and  
humidity**

EIA-364-31

Cycle the connector between 25 °C ±3 °C at 80 % ±3% RH and 65 °C ±3 °C at 50 % ±3% RH. Ramp times should be 0.5 hour and dwell times should be 1.0 hour. Dwell times start when the temperature and humidity have stabilized within the specified levels. Perform 24 such cycles.



None

**6**
**Low level contact  
resistance**

EIA-364-23

The measurement is made across the plug and receptacle mated contacts and does not include any internal paddle cards or substrates of the plug or receptacle.

50 milliohms max.

**7**
**Reseating**

Manually unplug/plug the connector or socket. Perform 3 such cycles.

No evidence of  
physical damage


**8**
**Low level contact  
resistance**

EIA-364-23

The measurement is made across the plug and receptacle mated contacts and does not include any internal paddle cards or substrates of the plug or receptacle.



50 milliohms max.


**Test Group A-3 (required for all connectors)**

| Item | Test                                      | Test procedure   | Test criteria   |
|------|---|--|---|
| 1    | <b>Low level contact resistance</b>       | EIA-364-23<br>The measurement is made across the plug and receptacle mated contacts and does not include any internal paddle cards or substrates of the plug or receptacle.  | 40 milliohms max for all contacts.<br>Baseline measurement.   |
| 2    | <b>Durability (preconditioning)</b>       | EIA-364-09<br>Perform 50 unplug/plug cycles.   | No evidence of physical damage  |
| 3    | <b>Temperature life (preconditioning)</b> | EIA-364-17, method A<br>105° C without applied voltage for 72 hours when used as preconditioning.  | None  |
| 4    | <b>Low level contact resistance</b>       | EIA-364-23<br>The measurement is made across the plug and receptacle mated contacts and does not include any internal paddle cards or substrates of the plug or receptacle.  | 50 milliohms max.   |
| 5    | <b>Vibration</b>                          | EIA-364-28, test condition VII, test condition letter D<br>15 minutes in each of 3 mutually perpendicular directions. Both mating halves should be rigidly fixed so as not to contribute to the relative motion of one contact against another.<br> | No evidence of physical damage.<br>No discontinuities of 1 $\mu$ s or longer duration when mated connector during test. |
| 6    | <b>Low level contact resistance</b>       | EIA-364-23<br>The measurement is made across the plug and receptacle mated contacts and does not include any internal paddle cards or substrates of the plug or receptacle.  | 50 milliohms max.   |



**Test Group A-4 (required for all connectors)**

| Item          | Test  | Test procedure  | Test criteria   |                 |                  |                 |  |  |  |               |          |             |                    |  |  |  |       |   |    |                 |                 |                  |                 |    |      |      |      |        |      |        |      |
|---------------|---|---|---|-----------------|------------------|-----------------|--|--|--|---------------|----------|-------------|--------------------|--|--|--|-------|---|----|-----------------|-----------------|------------------|-----------------|----|------|------|------|--------|------|--------|------|
| 1             | Low level contact resistance  | EIA-364-23<br>The measurement is made across the plug and receptacle mated contacts and does not include any internal paddle cards or substrates of the plug or receptacle.   | 40 milliohms max for all contacts.<br>Baseline measurement. |                 |                  |                 |  |  |  |               |          |             |                    |  |  |  |       |   |    |                 |                 |                  |                 |    |      |      |      |        |      |        |      |
| 2             | Durability (preconditioning)  | EIA-364-09<br>Perform 50 unplug/plug cycles.  | No evidence of physical damage                              |                 |                  |                 |  |  |  |               |          |             |                    |  |  |  |       |   |    |                 |                 |                  |                 |    |      |      |      |        |      |        |      |
| 3             | Temperature life (preconditioning)                                    | EIA-364-17, method A<br>105° C without applied voltage for 72 hours when used as preconditioning.   | None  |                 |                  |                 |  |  |  |               |          |             |                    |  |  |  |       |   |    |                 |                 |                  |                 |    |      |      |      |        |      |        |      |
| 4             | Low level contact resistance  | EIA-364-23<br>The measurement is made across the plug and receptacle mated contacts and does not include any internal paddle cards or substrates of the plug or receptacle.   | 50 milliohms max.   |                 |                  |                 |  |  |  |               |          |             |                    |  |  |  |       |   |    |                 |                 |                  |                 |    |      |      |      |        |      |        |      |
| 5             | Mixed flowing gas ( Only for 30u” Au and 2u” Au + 30u” NiPd plating ) | EIA-364-65, class II Condition A<br><br>-Mate state (5pcs)<br><div></div><br>-Unmate state (5pcs)<br><div></div><br><table border="1"><thead><tr><th colspan="3">Relative</th><th colspan="4">Rollutant</th></tr><tr><th>Environmental</th><th>Humidity</th><th>Temperature</th><th colspan="4">Concentration, ppb</th></tr><tr><th>Class</th><th>%</th><th>°C</th><th>Cl<sub>2</sub></th><th>NO<sub>2</sub></th><th>H<sub>2</sub>S</th><th>SO<sub>2</sub></th></tr></thead><tbody><tr><td>II</td><td>70±2</td><td>30±1</td><td>10±3</td><td>200±50</td><td>10±5</td><td>100±20</td></tr></tbody></table> | Relative  |                 |                  | Rollutant       |  |  |  | Environmental | Humidity | Temperature | Concentration, ppb |  |  |  | Class | % | °C | Cl <sub>2</sub> | NO <sub>2</sub> | H <sub>2</sub> S | SO <sub>2</sub> | II | 70±2 | 30±1 | 10±3 | 200±50 | 10±5 | 100±20 | None |
| Relative      |   |   | Rollutant   |                 |                  |                 |  |  |  |               |          |             |                    |  |  |  |       |   |    |                 |                 |                  |                 |    |      |      |      |        |      |        |      |
| Environmental | Humidity  | Temperature   | Concentration, ppb  |                 |                  |                 |  |  |  |               |          |             |                    |  |  |  |       |   |    |                 |                 |                  |                 |    |      |      |      |        |      |        |      |
| Class         | %   | °C  | Cl <sub>2</sub>   | NO <sub>2</sub> | H <sub>2</sub> S | SO <sub>2</sub> |  |  |  |               |          |             |                    |  |  |  |       |   |    |                 |                 |                  |                 |    |      |      |      |        |      |        |      |
| II            | 70±2  | 30±1  | 10±3  | 200±50          | 10±5             | 100±20          |  |  |  |               |          |             |                    |  |  |  |       |   |    |                 |                 |                  |                 |    |      |      |      |        |      |        |      |
| 6             | Low level contact resistance  | EIA-364-23<br>The measurement is made across the plug and receptacle mated contacts and does not include any internal paddle cards or substrates of the plug or receptacle.   | 50 milliohms max.   |                 |                  |                 |  |  |  |               |          |             |                    |  |  |  |       |   |    |                 |                 |                  |                 |    |      |      |      |        |      |        |      |

|    |                                     |   |                                |
|----|-------------------------------------|---|--------------------------------|
| 7  | <b>Thermal disturbance</b>          | <p>Cycle the connector or socket between 15 °C ±3 °C and 85 °C ± 3 °C, as measured on the part. Ramps should be a minimum of 2 °C per minute, and dwell times should insure that the contacts reach the temperature extremes (a minimum of 5 minutes). Humidity is not controlled. Perform 10 such cycles.</p> <p>Temperature</p>  <p>Time</p> <p>As one cycle, total 10 cycles</p> | None                           |
| 8  | <b>Low level contact resistance</b> | <p>EIA-364-23<br/>The measurement is made across the plug and receptacle mated contacts and does not include any internal paddle cards or substrates of the plug or receptacle.</p>   | 50 milliohms max.              |
| 9  | <b>Reseating</b>                    | <p>Manually unplug/plug the connector or socket. Perform 3 such cycles.</p>   | No evidence of physical damage |
| 10 | <b>Low level contact resistance</b> | <p>EIA-364-23<br/>The measurement is made across the plug and receptacle mated contacts and does not include any internal paddle cards or substrates of the plug or receptacle.</p>   | 50 milliohms max.              |

**Test Group A-7 (EIA test groups A-5 and A-6 do not apply to this connector)**

| Item | Test                                   | Test procedure   | Test criteria   |
|------|--|--|---|
| 1    | <b>Dielectric withstanding voltage</b> | EIA-364-20, 100 VAC (RMS)<br>Perform 4 plug/unplug cycles.   | No disruptive discharge<br>Current leakage: 1 mA max.       |
| 2    | <b>Low level contact resistance</b>    | EIA-364-23<br>The measurement is made across the plug and receptacle mated contacts and does not include any internal paddle cards or substrates of the plug or receptacle.  | 40 milliohms max.   |
| 3    | <b>Durability (preconditioning)</b>    | EIA-364-09<br>Perform 4 unplug/plug cycles, followed by an unplug.   | No evidence of physical damage.                             |
| 4    | <b>Insertion force</b>                 | EIA 364-13<br>At a maximum rate of 12.5 mm (0.492") per minute.<br>(Total:5 cycles)  | Within the range of 5 N to 20 N.                            |
| 5    | <b>Extraction force</b>                | EIA 364-13<br>At a maximum rate of 12.5mm (0.492") per minute.<br>(Total:6 cycles)   | Within the range of 8 N to 20 N.                            |
| 6    | <b>Durability</b>                      | EIA 364-9<br>Perform 25 plug/unplug cycles. Cycle rate of 500 ± 50 cycles per hour followed by a plug.<br>(Total:31 cycles)  | No evidence of physical damage                              |
| 7    | <b>Extraction force</b>                | EIA 364-13<br>At a maximum rate of 12.5mm (0.492") per minute<br>(Total:32 cycles)   | Within :<br>- 33% of the initial reading.<br>- 8 N to 20 N. |
| 8    | <b>Durability</b>                      | EIA 364-9<br>Perform 2,468 plug/unplug cycles. (Total:2500 cycles)<br>Rotate the receptacle or plug 180° and perform 2,500 plug/unplug cycles.<br>Cycle rate of 500 +/-50 cycles per hour (total of 10,000 plug/unplug cycles, flipping every 2,500 cycles). | No evidence of physical damage                              |
| 9    | <b>Extraction force</b>                | EIA 364-13<br>At a maximum rate of 12.5mm (0.492") per minute  | Within 6 N to 20 N.   |

**TITLE: 0.5 MM PITCH USB TYPE C CONN.**

RELEASE DATE: 2023.05.03


8REVISION: C

ECN No: ECN-012221


PAGE: **20** OF **25**

|    |  |   |   |
|----|--|---|---|
| 10 | <b>Low level contact resistance</b>    | EIA-364-23<br>The measurement is made across the plug and receptacle mated contacts and does not include any internal paddle cards or substrates of the plug or receptacle. | 50 milliohms max.   |
| 11 | <b>Dielectric withstanding voltage</b> | EIA-364-20, 100 VAC (RMS)   | No disruptive discharge.<br>Current leakage: 1 mA max.  |
| 12 | <b>Insulation Resistance</b>           | EIA 364-21.<br>Mated and unmated connectors, apply 500 V DC between adjacent terminals.<br>Applicable to both receptacle and plug.  | A minimum of 100 MΩ insulation resistance is required between adjacent contacts of unmated and mated connectors |


### Test Group B-1: Type-C Connector and Cable Assembly Mechanical Tests

| Item  | Test   | Test procedure  | Test criteria   |  |  |             |    |      |          |   |      |  |
|---|--|---|---|--|--|-------------|----|------|----------|---|------|--|
| B-1-4   | 4-Axis Continuity                                    | <p>-The PCB shall be clamped on three sides of the receptacle no further than 5 mm away from the receptacle outline.</p> <p>- 5 mm ball tipped probe applied the force</p> <p>- Duration : 10 seconds</p> <p>- Direction: four directions (i.e., left, right, up, and down).</p>  <p style="text-align: center;"><b>Force and Moment Requirements</b></p> <table><tr><th>Receptacle configuration with respect to mounting surface</th><th>Force at 15 mm from receptacle shell mating edge (N)</th><th>Moment with respect to receptacle shell mating edge (Nm)</th></tr><tr><td>Right angle</td><td>20</td><td>0.30</td></tr><tr><td>Vertical</td><td>8</td><td>0.12</td></tr></table> | Receptacle configuration with respect to mounting surface | Force at 15 mm from receptacle shell mating edge (N) | Moment with respect to receptacle shell mating edge (Nm) | Right angle | 20 | 0.30 | Vertical | 8 | 0.12 | No discontinuities greater than 1 microsecond duration in any of the four orientations tested. |
| Receptacle configuration with respect to mounting surface | Force at 15 mm from receptacle shell mating edge (N) | Moment with respect to receptacle shell mating edge (Nm)  |   |  |  |             |    |      |          |   |      |  |
| Right angle   | 20   | 0.30  |   |  |  |             |    |      |          |   |      |  |
| Vertical  | 8  | 0.12  |   |  |  |             |    |      |          |   |      |  |

## Test Group B-5: Critical Dimensions

| Item  | Test                            | Test procedure   | Test criteria  |
|-------|---------------------------------|--|--|
| B-5-1 | Critical Dimensions             | See customer drawing   | N/A  |
| B-5-2 | EMC Shielding Spring Inspection | <p>Visual inspection for compliance with Figure.</p>  <p>EMC shielding spring finger tip<br/>(Not exposed in plug housing opening.<br/>Applies to all EMC shielding springs)<br/><b>COMPLIANT</b></p> <p>(1.300 +/- 0.025mm)<br/>Plug housing opening</p> <p>Plug Housing Wall</p> <p>EMC shielding spring finger tip<br/>(Exposed in plug housing opening – one<br/>or more occurrences, any location)<br/><b>NONCOMPLIANT</b></p> <p>(1.300 +/- 0.025mm)<br/>Plug housing opening</p> | <p>No EMC shielding spring finger tip of the USB Full-Featured Type-C plug or USB 2.0 Type-C plug shall be exposed in the plug housing opening of the unmated Type-C plug.</p> |


## Test Group B-6: Connector Pair Current Rating

| Item | Test                   | Test procedure  | Test criteria   |
|------|------------------------|---|---|
| B-6  | Contact Current Rating | <p>Mate connector: measure the temperature rise at rated current after:<br/> A current of 9 A shall be applied collectively to <math>V_{BUS}</math> pins (i.e., pins A4, A9, B4, and B9) and 1.25 A shall be applied to the <math>V_{CONN}</math> pin (i.e., B5) as applicable, terminated through the corresponding GND pins (i.e., pins A1, A12, B1, and B12). A minimum current of 0.25 A shall also be applied individually to all the other contacts<br/> The ambient condition is still air at 25° C (EIA-364-70 METHOD 2)</p>  | <p>When current is applied to the contacts, the temperature rise shall not exceed 30°C at the outside surface of the shell. This requirement applies to the USB Type-C connector mated pair only.</p> |


Current Rating Test PCB

| Item                     | Trace width (mm) | Trace length (mm) on each PCB | Thickness            |
|--------------------------|------------------|-------------------------------|----------------------|
| Signal trace             | 0.25 max.        | 13 max.                       | 70 µm (2 oz. copper) |
| Ground trace             | 1.57 max.        | 38 max.                       | 70 µm (2 oz. copper) |
| $V_{BUS}$ and $V_{CONN}$ | 1.25 max.        | 30 max.                       | 70 µm (2 oz. copper) |
| PCB                      | N/A              | N/A                           | 0.80 - 1.20 mm       |

## Test Group B-7: Plug Connector Wrenching Test

| Item  | Test                            | Test procedure   | Test criteria   |
|-------|---------------------------------|--|---|
| B-7-1 | Wrenching Test                  | <ul style="list-style-type: none"> <li>- Plug only</li> <li>- Direction: four directions (i.e., left, right, up, and down).</li> <li>- Duration: 10 seconds</li> </ul>  <p>Wrenching Strength Test Fixture</p> <p>Receptacle Mating Datum A</p> <p>DETAIL B</p> <p>0.80 WALL THICKNESS</p> <p>6.20±0.02</p> | <p>The plug shall be mated with the continuity test fixture after the test forces have been applied to verify no damage has occurred that causes discontinuity or shorting.</p> <p>No plug damage: 0.75 Nm.<br/>No discontinuity or short after the test force applied.</p> |
| B-7-2 | Continuity                      |  |   |
| B7-3  | Dielectric withstanding voltage | Mated, 100 VAC (RMS)   | No disruptive discharge.<br>Current leakage: 1 mA max.  |

**B-7-4 Wrenching Test**



The plug shall disengage from the test fixture or mechanically fail when a moment of 2.0 Nm is applied in the up and down directions and a moment 3.5 Nm is applied in the left and right directions.

Example of Wrenching Strength Test Mechanical failure point



## 8 HOT AIR REFLOW CONDITION

### 8.1. Lead-free Process

TEMPERATURE CONDITION GRAPH  
(TEMPERATURE ON BOARD PATTERN SIDE)

