



## SPECIFICATION

宏致電子股份有限公司

桃園縣中壢市東園路13號

No.13, Dongyuan Rd., Zhongli City,

Taoyuan County 320, Taiwan (R.O.C.)

TEL: +886-3-463-2808

FAX: +886-3-463-1800

**SPEC. NO.:** PS-50578-XXXXX-XXX      **REVISION:** D

**PRODUCT NAME:** 1.0 mm Pitch FPC Connector

**PRODUCT NO:** 50578 , 50579 , 50580 , 50581 , 50582 , 50583 , 50584 ,  
50585 , 50586 , 50587 , 50588 , 50589 , 50590 , 50591 ,  
50592 , 50593series.

<b>PREPARED:</b>  <b>COCOYU</b>  <b>DATE:</b> <b>2015.12.12</b>	<b>CHECKED:</b>  <b>BRAVE</b>  <b>DATE:</b> <b>2015.12.12</b>	<b>APPROVED:</b>  <b>FRANK</b>  <b>DATE:</b> <b>2015.12.12</b>
--	--	---



Aces P/N: **50578series**

TITLE: **1.0 MM PITCH FPC CONNECTOR**

RELEASE DATE: 2015/12/12

REVISION: D

ECN No: ECN-1512176

PAGE: **2** OF **10**

1	REVISION HISTORY .....	3
2	SCOPE .....	4
3	APPLICABLE DOCUMENTS.....	4
4	REQUIREMENTS .....	4
5	PERFORMANCE .....	5
6	INFRARED REFLOW CONDITION .....	8
7	PRODUCT QUALIFICATION AND TEST SEQUENCE.....	9



Aces P/N: **50578series**

TITLE: **1.0 MM PITCH FPC CONNECTOR**

RELEASE DATE: 2015/12/12

REVISION: D

ECN No: ECN-1512176

PAGE: **3** OF **10**

## 1 Revision History

Rev.	ECN #	Revision Description	Prepared	Date
O	ECN-0812016	NEW PROJECT SPEC	JASON	2008/12/05
A	ECN-0908013	REVISED FPC RETENTION FORCE · CONTACT RETENTION FORCE · FITTING NAIL /HOUSING RETENTION FORCE	JASON	2009/08/03
B	ECN-0910290	REVISED RESISTANCE TO SOLDERING HEAT	JASON	2009/10/22
C	ECN-1401261	ADD WORKING VOLTAGE	XUFEI	2014/01/15
D	ECN-1512176	ADD FPC RETENTION FORCE AFTER DURABILITY	COCOYU	2015/12/12

TITLE: **1.0 MM PITCH FPC CONNECTOR**

RELEASE DATE: 2015/12/12

REVISION: D

ECN No: ECN-1512176

PAGE: **4** OF **10**

## 2 SCOPE

This specification covers performance, tests and quality requirements for **1.0 mm Pitch FPC Connector**. These connectors are used to hold graphic card in computer.

Aces's P/N : **50578series** , **50579series** , **50580series** , **50581series** , **50582series** ,  
**50583series** , **50584series** , **50585series** , **50586series** , **50587series** ,  
**50588series** , **50589series** , **50590series** , **50591series** , **50592series** ,  
**50593series** ,

## 3 APPLICABLE DOCUMENTS

**EIA-364** ELECTRONICS INDUSTRIES ASSOCIATION

## 4 REQUIREMENTS

### 4.1 Design and Construction

Product shall be of design, construction and physical dimensions specified on applicable product drawing.

### 4.2 Materials and Finish

- 4.2.1 Contact: High performance copper alloy (**Phosphor Bronze**)  
Finish: **Plating pls. See the product drawing.**
- 4.2.2 Housing: Thermoplastic High Temp., UL94V-0
- 4.2.3 Latch: Thermoplastic High Temp., UL94V-0
- 4.2.4 Fitting nail: **Copper Alloy, Plating pls. See the product drawing.**

### 4.3 Ratings

- 4.3.1 Working voltage less than 36 volts (per pin)
- 4.3.2 Voltage: **50 Volts AC (per pin)**
- 4.3.3 Current: **0.5 Amperes (per pin)**
- 4.3.4 Operating Temperature : **-40°C to +80°C**

TITLE: **1.0 MM PITCH FPC CONNECTOR**

RELEASE DATE: 2015/12/12

REVISION: D

ECN No: ECN-1512176

PAGE: **5** OF **10**

## 5 Performance

### 5.1. Test Requirements and Procedures Summary

Item	Requirement	Standard
Examination of Product	Product shall meet requirements of applicable product drawing and specification.	Visual, dimensional and functional per applicable quality inspection plan.
<b>ELECTRICAL</b>		
Item	Requirement	Standard
Low-signal Level Contact Resistance	<b>55 m Ω</b> Max.(initial)per contact <b>20 m Ω</b> Max. Change allowed	Mate connectors, measure by dry circuit, <b>20mV</b> Max., <b>100mA</b> Max.(EIA-364-23)
Insulation Resistance	<b>100 M Ω</b> Min.	Unmated connectors, apply <b>500 V</b> DC between adjacent terminals. (EIA-364-21)
Dielectric Withstanding Voltage	<b>250 VAC</b> Min. at sea level for <b>1</b> minute. No discharge, flashover or breakdown. Current leakage: <b>1 mA</b> max.	Test between adjacent contacts of unmated connectors. (EIA-364-20)
Temperature rise	<b>30°C</b> Max. Change allowed	Mate connector: measure the temperature rise at rated current after: <b>0.5 A</b> /Power contact. The temperature rise above ambient shall not exceed <b>30°C</b> The ambient condition is still air at <b>25°C</b> (EIA-364-70 METHOD 2)
<b>MECHANICAL</b>		
Item	Requirement	Standard
Durability	<b>30</b> cycles.	The sample should be mounted in the tester and fully mated and unmated the number of cycles specified at the rate of <b>25.4 ± 3mm/min.</b> (EIA-364-09)
Contact Retention Force	<b>0.30kgf</b> Min.	Operation Speed : <b>25.4 ± 3</b> mm/minute. Measure the contact retention force with Tensile strength tester.
Actuator Insertion / Extration Force	Refer to Refer to Actuator Insertion/Extration Force	Mate applicable FPC insert and extract actuator at the speed of <b>25 ± 3</b> mm/min.
FPC Retention Force	<b>1st :50gf/pin MIN</b> <b>30 th:35gf/pin MIN</b>	Insert the actuator, pull the FPC at the speed rate of <b>25.4 ± 3</b> mm/min.
Fitting Nail /Housing Retention Force	<b>0.30kgf</b> MIN.	Apply axial pull out force at the speed rate of <b>25.4 ± 3</b> mm/minute. On the fitting nail assembled in the housing.

**TITLE: 1.0 MM PITCH FPC CONNECTOR**

RELEASE DATE: 2015/12/12

REVISION: D

ECN No: ECN-1512176

PAGE: **6** OF **10**

<p>Vibration</p>	<p>1 <math>\mu</math>s Max.</p>	<p>The electrical load condition shall be 100 mA maximum for all contacts. Subject to a simple harmonic motion having amplitude of 0.76mm (1.52mm maximum total excursion) in frequency between the limits of <b>10 and 55 Hz</b>. The entire frequency range, from <b>10 to 55 Hz</b> and return to <b>10 Hz</b>, shall be traversed in approximately 1 minute. This motion shall be applied for 2 hours in each of three mutually perpendicular directions. (EIA-364-28 Condition I)</p>
<p>Shock (Mechanical)</p>	<p>1 <math>\mu</math>s Max.</p>	<p>Subject mated connectors to <b>50 G's</b> (peak value) <b>half-sine</b> shock pulses of <b>11</b> milliseconds duration. Three shocks in each direction shall be applied along the three mutually perpendicular axes of the test specimen (18 shocks). The electrical load condition shall be 100mA maximum for all contacts. (EIA-364-27, test condition A)</p>

**ENVIRONMENTAL**

Item	Requirement	Standard
<p>Resistance to <b>Reflow</b> Soldering Heat</p>	<p>See Product Qualification and Test Sequence Group 9</p>	<p>Pre Heat : 150°C Max, 90sec Min. Heat : 200°C Min., 30sec Min. Peak Temp. : 230°C Max, 3sec Min.  See 6.1 General process</p>
<p>Resistance to <b>Reflow</b> Soldering Heat</p>	<p>See Product Qualification and Test Sequence Group 9 (<b>Lead Free</b>)</p>	<p>Pre Heat : 150°C~180°C, 60~90sec. Heat : 230°C Min., 40sec Min. Peak Temp. : 260°C Max, 10sec Max.  See 6.2 Lead free process</p>
<p>Thermal Shock</p>	<p>See Product Qualification and Test Sequence Group 3</p>	<p>Mate module and subject to follow condition for 5 cycles. 1 cycles: -40 +0/-3 °C, 30 minutes +80 +3/-0 °C, 30 minutes (EIA-364-32, test condition A)</p>
<p>Humidity</p>	<p>See Product Qualification and Test Sequence Group 3</p>	<p>Mated Connector 40°C, 90~95% RH, Reefer to Method II. (EIA-364-31, Test condition A)</p>

**TITLE: 1.0 MM PITCH FPC CONNECTOR**

RELEASE DATE: 2015/12/12

REVISION: D

ECN No: ECN-1512176


PAGE: **7** OF **10**

Temperature life	See Product Qualification and Test Sequence Group 4	Subject mated connectors to temperature life at 85°C for 96 hours. Measure Signal. (EIA-364-17, Test condition A)
Salt Spray	See Product Qualification and Test Sequence Group 5	Subject mated/unmated connectors to 5% salt-solution concentration, 35°C for 8 hours. (EIA-364-26, Test condition B)
Solder ability	Solder able area shall have minimum of 95% solder coverage.	Subject the test area of contacts into the flux for 5-10 sec. And then into solder bath, Temperature at 245 ±5°C, for 4-5 sec. (EIA-364-52)
Resistance to Soldering Heat	No deformation of components affecting performance.	350c±5c for 5 seconds


**Note.** Flowing Mixed Gas shall be conducted by customer request.

## 6 INFRARED REFLOW CONDITION

### 6.1. General Process



### 6.2. Lead-free Process





TITLE: **1.0 MM PITCH FPC CONNECTOR**

RELEASE DATE: 2015/12/12

REVISION: D

ECN No: ECN-1512176

PAGE: **9** OF **10**

## 7 PRODUCT QUALIFICATION AND TEST SEQUENCE

Test or Examination	Test Group									
	1	2	3	4	5	6	7	8	9	10
	Test Sequence									
Examination of Product	1、3	1、8	1、7	1、6	1、4				1	
Low-signal Level Contact Resistance		2、11	2、10	2、9	2、5				3	1、4
Insulation Resistance		3、10	3、9	3、8						
Dielectric Withstanding Voltage		4、9	4、8	4、7						
Temperature rise	2									
Durability		6								
Vibration										2
Shock (Mechanical)										3
Thermal Shock			5							
Humidity			6							
Temperature life				5						
Salt Spray					3					
Solder ability						1				
Contact Retention Force							1			
FPC Retention Force		5、7								
Fitting Nail /Housing Retention Force								1		
Resistance to Soldering Heat									2	
Sample Size	2	4	4	4	4	2	4	4	4	4

TITLE: **1.0 MM PITCH FPC CONNECTOR**

RELEASE DATE: 2015/12/12

REVISION: D

ECN No: ECN-1512176

PAGE: **10** OF **10**

**Actuator Insertion/Extraction Force**

NO. OF Ckt.	Insertion Force ( Kgf, Max )	Extraction Force ( Kgf, Min )	
4	2.90	0.30	
5	3.00		
6	3.10		
7	3.20		
8	3.30		
9	3.40		
10	3.50		
11	3.60		0.33
12	3.70		0.36
13	3.80		0.39
14	3.90	0.42	
15	4.00	0.45	
16	4.10	0.48	
17	4.20	0.51	
18	4.30	0.54	
19	4.40	0.57	
20	4.50	0.60	
21	4.60	0.63	
22	4.70	0.66	
23	4.80	0.69	
24	4.90	0.72	
25	5.00	0.75	
26	5.10	0.78	
27	5.20	0.81	
28	5.30	0.84	
29	5.40	0.87	
30	5.50	0.90	
31	5.60	0.93	
32	5.70	0.96	
33	5.80	0.99	
34	5.90	1.02	