



SPECIFICATION

宏致電子股份有限公司

桃園縣中壢市東園路13號

No.13, Dongyuan Rd., Jhongli City,

Taoyuan County 320, Taiwan (R.O.C.)

TEL: +886-3-463-2808

FAX: +886-3-463-1800

SPEC. NO.: PS-52900-XXXXX-XXX

REVISION: B

PRODUCT NAME: POWER ACCESS CONN.

PRODUCT NO: 5290X-XXXXXXXX-XXX

PREPARED: MARK DATE: 2015/09/04	CHECKED: ERIC DATE: 2015/09/04	APPROVED: GRAND DATE: 2015/09/04
--	---	---



TITLE: POWER ACCESS CONNECTOR

RELEASE DATE: 2015.09.04

REVISION: B

ECN No: 1509012

PAGE: 2 OF 9

1	REVISION HISTORY	3
2	SCOPE	4
3	APPLICABLE DOCUMENTS	4
4	REQUIREMENTS	4
5	PERFORMANCE	5
6	PRODUCT QUALIFICATION AND TEST SEQUENCE.....	8
7	LEAD-FREE PROCESS:.....	9



TITLE: POWER ACCESS CONNECTOR

RELEASE DATE: 2015.09.04

REVISION: B

ECN No: 1509012

PAGE: 3 OF 9

1 Revision History

Rev.	ECN #	Revision Description	Prepared	Date
1	ECN-1204334	NEW SPEC	SIMON	2012.06.20
O	ECN-1208427	RELEASE	SIMON	2012.06.29
A	ECN-1505221	ADD TUV CERTIFICATION	SIMON	2015.05.26
B	ECN-1509012	MODIFY MATING/UNMATING FORCE	MARK	2015.09.01

TITLE: POWER ACCESS CONNECTOR

RELEASE DATE: 2015.09.04

REVISION: B

ECN No: 1509012

PAGE: 4 OF 9

2 SCOPE

This specification defines the performance, test, quality and reliability requirements of Right Angle (R/A) Power Access connector product that will mate to a separable power Access at end application.

3 APPLICABLE DOCUMENTS

3.1 EIA-364-TP70: ELECTRONICS INDUSTRIES ASSOCIATION

3.2 SAFETY AGENCY APPROVALS

CUL / UL File Number : 12CA38547

TUV Certification: B 13 09 85359 001

4 REQUIREMENTS

4.1 Design and Construction

4.1.1 Product shall be of design, construction and physical dimensions specified on applicable product drawing.

4.1.2 All materials conform to R.o.H.S. and the standard depends on TQ-WI-140101.

4.2 Materials and Finish

The material for each part shall be as specified herein or equivalent. The substitute material shall meet the performance requirement of this specification.

4.2.1 Power Contact: High conductivity copper alloy
Finish: (a) Contact Area: Refer to the drawing.
(b) Under plate: Refer to the drawing.
(c) Solder area: Refer to the drawing.

4.2.2 Signal Contact: copper alloy
Finish: (a) Contact Area: Refer to the drawing.
(b) Under plate: Refer to the drawing.
(c) Solder area: Refer to the drawing.

4.2.3 Housing dielectric material:
(a) Material: High temperature thermoplastic, glass-filled.
(b) Flame level: UL94V-0 rated.

4.3 Ratings

4.3.1 Voltage: 600 Volts AC / DC

4.3.2 Current Rating :

4.3.2.1 Power pin 60A full on compliant with UL certification

4.3,2,2 Signal pin 3A full on compliant with UL certification

4.3.2.3 Power pin 35A full on compliant with CUL certification

4,3,2,4 Signal pin 1.5A full on compliant with CUL certification

4.3.3 Operating Temperature : -40°C to +125°C (including T-rise from applied current)
Non- Operating Temperature : -40°C to +125°C

TITLE: POWER ACCESS CONNECTOR

RELEASE DATE: 2015.09.04

REVISION: B

ECN No: 1509012

PAGE: 5 OF 9

5 Performance

5.1. Test Requirements and Procedures Summary

Item	Requirement	Standard
Examination of Product	Product shall meet requirements of applicable product drawing and specification.	Visual, dimensional and functional per applicable quality inspection plan.
ELECTRICAL		
Low Level Contact Resistance	Power contact Not exceed 1 mΩ , initial; and less than 0.5 mΩ changes after test. Signal contact Not exceed 25 mΩ , initial; and less than 12.5 mΩ changes after test.	Mate connectors, measure by dry circuit, 20mV Max., 100mA Max. (EIA-364-23)
Insulation Resistance	Initial 5,000 MΩ Min; and 500 MΩ Min. after test.	Apply with a test voltage of 500 VDC between the closet adjacent contacts. (EIA-364-21)
Dielectric Withstanding Voltage	No discharge, flashover or breakdown. Current leakage: 0.5 mA max.	Apply with a test voltage of 2500V /RMS for power contact and 1000V /RMS for signal contact. (EIA-364-20)
Temperature Rise	30°C T-Rise Max For CUL 60°C T-Rise Max For UL	Mate connector: measure the temperature rise at rated current until temperature stable the ambient condition is still air at 30°C

TITLE: POWER ACCESS CONNECTOR

RELEASE DATE: 2015.09.04

REVISION: B

ECN No: 1509012

PAGE: 6 OF 9

MECHANICAL		
Item	Requirement	Standard
Retention Force Into the housing	700gf pre all power pin Min. 300gf pre all signal pin Min. 500gf pre fitting nail Min.	Operation Speed: 25.4 ± 3 mm/minute. Measure the contact retention force with Tensile strength tester.
Normal force	350gf pre male power pin Min. 35gf pre female signal pin Min.	Apply perpendicular force to terminal at rate of 25.4 ± 3mm/min.
Durability	There shall be no damage after 250 cycles.	The sample should be mounted in the tester and fully mated and unmated the number of cycles specified at the rate of 25.4 ± 3mm/min. (EIA-364-09)
Mating force	900g (Max.) /Per Pin for power 150g (Max.) /Per Pin for signal	Operation Speed: 25.4 ± 3 mm/minute.. Measure the force required to mate/Unmate connector. (EIA-364-13)
Unmating force	230g (Min.)/Per Pin for power 18g (Min.)/Per Pin for signal.	Operation Speed: 25.4 ± 3 mm/minute.. Measure the force required to mate/Unmate connector. (EIA-364-13)
Shock (Mechanical)	1 μs Max.	Subject mated connectors to 50 G's (peak value) half-sine shock pulses of 11 milliseconds duration. Three shocks in each direction shall be applied along the three mutually perpendicular axes of the test specimen (18 shocks). The electrical load condition shall be 100mA maximum for all contacts. (EIA-364-27, test condition A)
Vibration	Power contact: Not exceed 1 mΩ, initial; and less than 0.5 mΩ changes after test. Signal contact: Not exceed 25 mΩ, initial; and less than 12.5 mΩ changes after test.	The electrical load condition shall be 100 mA maximum for all contacts. Subject to a simple harmonic motion having amplitude of 0.76mm (1.52mm maximum total excursion) in frequency between the limits of 10 and 55 Hz. The entire frequency range, from 10 to 55 Hz and return to 10 Hz, shall be traversed in approximately 1 minute. This motion shall be applied for 2 hours in each of three mutually perpendicular directions. (EIA-364-28 Condition I)

TITLE: POWER ACCESS CONNECTOR

RELEASE DATE: 2015.09.04

REVISION: B

ECN No: 1509012

PAGE: 7 OF 9

ENVIRONMENTAL		
Item	Requirement	Standard
Thermal Shock	Power contact Not exceed 1 mΩ , initial; and less than 0.5 mΩ changes after test. Signal contact Not exceed 25 mΩ , initial; and less than 12.5 mΩ changes after test.	Mate module and subject to follow condition for 5 cycles. 1 cycles: -55 +0/-3 °C, 30 minutes +85 +3/-0 °C, 30 minutes (EIA-364-32, test condition I)
Humidity	Power contact Not exceed 1 mΩ , initial; and less than 0.5 mΩ changes after test. Signal contact Not exceed 25 mΩ , initial; and less than 12.5 mΩ changes after test.	Mated Connector 40°C, 90~95% RH, 96 hours. (EIA-364-31, Condition A, Method II)
Salt spray	No physical damages See Product Qualification and Test Sequence Group 5	Subject mated/unmated connectors to 5% salt-solution concentration, 35°C for 96 hours . (EIA-364-26)
Temperature life	Power contact Not exceed 1 mΩ , initial; and less than 0.5 mΩ changes after test. Signal contact Not exceed 25 mΩ , initial; and less than 12.5 mΩ changes after test.	Subject mated connectors to temperature life at 105°C for 240 hours . (EIA-364-17, Test condition A)
Solder ability	Tin plating: Solder able area shall have minimum of 95% solder coverage. Gold plating: Solder able area shall have minimum of 75% solder coverage	And then into solder bath, Temperature at 245 ±5°C , for 4-5 sec . (EIA-364-52)



TITLE: POWER ACCESS CONNECTOR

RELEASE DATE: 2015.09.04

REVISION: B

ECN No: 1509012

PAGE: 8 OF 9

6 PRODUCT QUALIFICATION AND TEST SEQUENCE

Test or Examination	Test Group								
	1	2	3	4	5	6	7		
	Test Sequence								
Examination of Product			1,7	1,6	1,4				
Low Level Contact Resistance	1,7	1,4	2,10	2,9	2,5				
Insulation Resistance			3,9	3,8					
Dielectric Withstanding Voltage			4,8	4,7					
Contact Retention Force							1		
Normal Force							2		
Durability	4								
Mating Force	2,5								
Unmating Force	3,6								
Shock (Mechanical)		3							
Vibration		2							
Thermal Shock			5						
Humidity			6						
Salt Spray					3				
Temperature Life				5					
Solder ability						1			
Sample Size	4	4	4	4	2	2	2		

TITLE: POWER ACCESS CONNECTOR

RELEASE DATE: 2015.09.04

REVISION: B

ECN No: 1509012

PAGE: 9 OF 9

7 LEAD-FREE PROCESS:

TEMPERATURE CONDITION GRAPH
(TEMPERATURE ON BOARD PATTERN SIDE)

