



## SPECIFICATION

宏致電子股份有限公司

桃園縣中壢市東園路13號

No.13, Dongyuan Rd., Jhongli City,

Taoyuan County 320, Taiwan (R.O.C.)

TEL: +886-3-463-2808

FAX: +886-3-463-1800

SPEC. NO.: PS-60289-XXXXX-XXX REVISION: B

PRODUCT NAME: 2.0mm PITCH FEMALE HEADER, PIN HEADER

PRODUCT NO: 60289, 60290, 603xx, 60xxx SERIES

PREPARED:	CHECKED:	APPROVED:
<b>LIAO WAN TING</b>	<b>TENG CHANG HO</b>	<b>KUO JUNG HSUN</b>
DATE: <b>2021.01.12</b>	DATE: <b>2021.01.12</b>	DATE: <b>2021.01.12</b>



Aces P/N: **60289 series**

TITLE: **2.0MM PITCH FEMALE HEADER, PIN HEADER CONNECTOR.**

RELEASE DATE: 2021/01/12

REVISION: B

ECN No: ECN-001954

PAGE: **2** OF **8**

1	REVISION HISTORY .....	3
2	SCOPE .....	4
3	APPLICABLE DOCUMENTS.....	4
4	REQUIREMENTS .....	4
5	PERFORMANCE .....	5
6	INFRARED REFLOW CONDITION .....	7
7	PRODUCT QUALIFICATION AND TEST SEQUENCE .....	8



Aces P/N: **60289** series

TITLE: **2.0MM PITCH FEMALE HEADER, PIN HEADER CONNECTOR.**

RELEASE DATE: 2021/01/12

REVISION: B

ECN No: ECN-001954

PAGE: **3** OF **8**

## 1 Revision History

Rev.	ECN #	Revision Description	Prepared	Date
O	ECN-1801488	NEW SPEC	LIAO WAN TING	2018.01.30
A	ECN-1809290	Add 603xx SERIES	LIAO WAN TING	2018.09.20
B	ECN-001954	Add 60xxx SERIES	LIAO WAN TING	2021.01.12

TITLE: **2.0MM PITCH FEMALE HEADER, PIN HEADER CONNECTOR.**

RELEASE DATE: 2021/01/12

REVISION: B

ECN No: ECN-001954

PAGE: **4** OF **8**

## 2 SCOPE

This specification covers performance, tests and quality requirements for [2.0mm pitch Female Header, Pin Header connector](#).

## 3 APPLICABLE DOCUMENTS

EIA-364: ELECTRONICS INDUSTRIES ASSOCIATION

## 4 REQUIREMENTS

### 4.1 Design and Construction

Product shall be of design, construction and physical dimensions specified on applicable product drawing.

### 4.2 Materials and Finish

4.2.1 Contact: [Refer to the drawing](#)

Finish: [Refer to the drawing](#).

4.2.2 Housing: [Refer to the drawing](#).

### 4.3 Ratings

4.3.1 Voltage: [30 Volts AC \(per pin\)](#)

4.3.2 Current: [2 Amperes Max. \(per pin\)](#)

4.3.3 Operating Temperature : [-40°C to +85°C](#)

**TITLE: 2.0MM PITCH FEMALE HEADER, PIN HEADER CONNECTOR.**

RELEASE DATE: 2021/01/12

REVISION: B

ECN No: ECN-001954

PAGE: **5** OF **8**

## 5 Performance

### 5.1. Test Requirements and Procedures Summary

Item	Requirement	Standard
Examination of Product	Product shall meet requirements of applicable product drawing and specification.	Visual, dimensional and functional per applicable quality inspection plan.
ELECTRICAL		
Item	Requirement	Standard
Low Level Contact Resistance	30 m $\Omega$ Max.	Mate connectors, measure by dry circuit, 20mV Max., 100mA Max. (EIA-364-23)
Insulation Resistance	1000 M $\Omega$ Min.	Unmated connectors, apply 500 V DC between adjacent terminals. (EIA-364-21)
Dielectric Withstanding Voltage	No discharge, flashover or breakdown. Current leakage: 5 mA max.	500 VAC Min. at sea level for 1 minute. Test between adjacent contacts of unmated connectors. (EIA-364-20)
Temperature Rise	30°C Max. Change allowed	Mate connector: measure the temperature rise at rated current until temperature stable. The ambient condition is still air at 25°C (EIA-364-70, METHOD1,CONDITION1)

MECHANICAL		
Item	Requirement	Standard
Durability	300 cycles	The sample should be mounted in the tester and fully mated and unmated the number of cycles specified at the rate of 25.4 $\pm$ 3mm/min. (EIA-364-09)
Mating / Unmating Forces	Mating Force: 350 gf Max./pin. Unmating Force: 20 gf Min./pin	Operation Speed : 25.4 $\pm$ 3 mm/minute.. Measure the force required to mate/unmate connector. (EIA-364-13)
Contact Retention Force (Before Reflow)	Pin Header: 300 gf Min. Female Header: 150 gf Min.	Operation Speed : 25.4 $\pm$ 3 mm/minute.. Measure the force required to mate/unmate connector. (EIA-364-13)

**TITLE: 2.0MM PITCH FEMALE HEADER, PIN HEADER CONNECTOR.**

RELEASE DATE: 2021/01/12

REVISION: B

ECN No: ECN-001954

PAGE: **6** OF **8**

<b>ENVIRONMENTAL</b>		
<b>Item</b>	<b>Requirement</b>	<b>Standard</b>
Resistance to <b>Reflow</b> Soldering Heat	See Product Qualification and Test Sequence Group <b>8 (Lead Free)</b>	Pre Heat : 150°C~180°C, 60~120sec. Heat : 230°C Min., 40sec Min. Peak Temp. : 260°C Max, 10sec Max.
Thermal Shock	See Product Qualification and Test Sequence Group <b>4</b>	Mate module and subject to follow condition for 5 cycles. 1 cycles: -55 +0/-3 °C, 30 minutes +85 +3/-0 °C, 30 minutes (EIA-364-32, test condition I)
Humidity	See Product Qualification and Test Sequence Group <b>4</b>	Mated Connector 40°C, 90~95% RH, 96 hours. (EIA-364-31, Condition A, Method II)
Temperature Life	See Product Qualification and Test Sequence Group <b>5</b>	Subject mated connectors to temperature life at <b>85°C</b> for <b>96</b> <b>hours</b> . (EIA-364-17, Test condition A)
Salt Spray (Only For Gold Plating)	See Product Qualification and Test Sequence Group <b>6</b>	Subject mated/unmated connectors to 5% salt-solution concentration, 35°C <b>Gold flash for 24 hours</b> (EIA-364-26)
Solder ability	Tin plating: Solder able area shall have minimum of 95% solder coverage. Gold plating: Solder able area shall have minimum of 75% solder coverage	And then into solder bath, Temperature at <b>245 ±5°C</b> , for <b>4-5</b> sec. (EIA-364-52)

TITLE: **2.0MM PITCH FEMALE HEADER, PIN HEADER CONNECTOR.**


RELEASE DATE: 2021/01/12

REVISION: B

ECN No: ECN-001954

PAGE: **7** OF **8**

## 6 INFRARED REFLOW CONDITION



**TITLE: 2.0MM PITCH FEMALE HEADER, PIN HEADER CONNECTOR.**

RELEASE DATE: 2021/01/12

REVISION: B

ECN No: ECN-001954

PAGE: **8** OF **8**

## 7 PRODUCT QUALIFICATION AND TEST SEQUENCE

Test or Examination	Test Group									
	1	2	3	4	5	6	7	8		
	Test Sequence									
Examination of Product				1、7	1、6	1、4		1		
Low Level Contact Resistance		1、5		2、10	2、9	2、5		3		
Insulation Resistance				3、9	3、8					
Dielectric Withstanding Voltage				4、8	4、7					
Temperature Rise	1									
Mating / Unmating Forces		2、4								
Durability		3								
Contact Retention Force (Before Reflow)			1							
Thermal Shock				5						
Humidity				6						
Temperature Life					5					
Salt Spray(Only For Gold Plating)						3				
Solder ability							1			
Resistance to Soldering Heat								2		
Sample Size	2	4	4	4	4	4	2	4		